



LOGO! CSM12/24 Compact Switch Module connection of a LOGO! (. .0BA7/...0BA8) and up to 3 further nodes to Ind. Ethernet with 10/100 Mbit/s Unmanaged switch, 4 RJ45 ports, 1x front port for diagnostics DC 12/24V power supply LED diagnostics, LOGO! setup.

|   |                        |
|---|------------------------|
| <b>product type designation</b>   | <b>LOGO! CSM 12/24</b> |
| <b>transfer rate</b>  |                        |
| transfer rate   | 10 Mbit/s, 100 Mbit/s  |
| <b>interfaces / for communication / maximum configuration for modular devices</b> |                        |
| number of electrical ports / maximum  | 4                      |
| <b>interfaces / for communication / integrated</b>                                |                        |
| number of electrical connections  | 4                      |
| • for network components or terminal equipment                                    |                        |
| number of 100 Mbit/s SC ports   | 0                      |
| • for multimode   |                        |
| number of 1000 Mbit/s LC ports  | 0                      |
| • for multimode   |                        |
| • for single mode (LD)  | 0                      |
| <b>interfaces / other</b>   |                        |
| number of electrical connections  | 1                      |
| • for power supply  |                        |
| type of electrical connection   | 3-pole terminal block  |
| • for power supply  |                        |
| <b>supply voltage, current consumption, power loss</b>                            |                        |
| <b>type of voltage / 1 / of the supply voltage</b>                                | DC                     |
| • supply voltage / 1 / rated value  | 24 V                   |
| • power loss [W] / 1 / rated value  | 1.5 W                  |
| • supply voltage / 1 / rated value  | 10.2 ... 30.2 V        |
| • consumed current / 1 / maximum  | 0.15 A                 |
| • type of electrical connection / 1 / for power supply                            | 3-pole terminal block  |
| • product component / 1 / fusing at power supply input                            | Yes                    |
| <b>ambient conditions</b>   |                        |
| ambient temperature   |                        |
| • during operation  | 0 ... 55 °C            |
| • during storage  | -40 ... +70 °C         |
| • during transport  | -40 ... +70 °C         |
| relative humidity   |                        |
| • at 25 °C / without condensation / during operation / maximum                    | 90 %                   |
| protection class IP   | IP20                   |
| <b>design, dimensions and weights</b>   |                        |
| design  | LOGO! module           |
| width   | 71.5 mm                |
| height  | 90 mm                  |
| depth   | 58.2 mm                |

|  |  |
|--|--|
| net weight   | 0.15 kg  |
| fastening method   |  |
| <ul style="list-style-type: none"> <li>• 35 mm top hat DIN rail mounting</li> <li>• wall mounting</li> <li>• S7-300 rail mounting</li> <li>• S7-1500 rail mounting</li> </ul>  | <ul style="list-style-type: none"> <li>Yes</li> <li>Yes</li> <li>No</li> <li>No</li> </ul>   |
| <b>product functions / management, configuration, engineering</b>  |  |
| product function   |  |
| <ul style="list-style-type: none"> <li>• multiport mirroring</li> </ul>  | No   |
| product function / switch-managed  | No   |
| <b>standards, specifications, approvals</b>  |  |
| standard   |  |
| <ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>   | UL 508, CSA C22.2 No. 142  |
| reference code   |  |
| <ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> <li>• according to IEC 81346-2:2019</li> </ul>  | <ul style="list-style-type: none"> <li>KF</li> <li>KFE</li> </ul>  |
| <b>standards, specifications, approvals / CE</b>   |  |
| certificate of suitability / CE marking  | Yes  |
| <b>standards, specifications, approvals / hazardous environments</b>   |  |
| standard / for hazardous zone  |  |
| <ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>  | ATEX: EN 60079-0 : 2009, EN 60079-15 :2010 (Directive 94/9/EC), IECEx: IEC 60079-0 :2011, IEC 60079-15 :2010<br>Haz-Loc ANSI/ISA 12.12.01: CL. I, Div2, Group A,B,C,D T4, CL I, Zone 2, Group IIC, T4, Ta=55°C   |
| certificate of suitability   |  |
| <ul style="list-style-type: none"> <li>• CCC / for hazardous zone according to GB standard</li> </ul>  | Yes  |
| <b>standards, specifications, approvals / other</b>  |  |
| certificate of suitability   |  |
| <ul style="list-style-type: none"> <li>• C-Tick</li> <li>• KC approval</li> </ul>  | <ul style="list-style-type: none"> <li>Yes</li> <li>No</li> </ul>  |
| <b>standards, specifications, approvals / marine classification</b>  |  |
| Marine classification association  |  |
| <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> </ul>                          | <ul style="list-style-type: none"> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> </ul>   |
| <b>further information / internet-Links</b>  |  |
| Internet-Link  |  |
| <ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul> | <ul style="list-style-type: none"> <li><a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a></li> <li><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a></li> <li><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></li> <li><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a></li> <li><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></li> <li><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></li> <li><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></li> </ul>  |
| <b>security information</b>  |  |
| security information   | Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4) |

last modified:

2/6/2023 

