

DT-179
Carbon Monoxide
Datalogger (P288)



DT-185
Light Datalogger (P287)



DT-186
Anemometer Datalogger (P287)



DT-171
Humidity & Temperature
Datalogger (P285)



DT-171V
DC Voltage Datalogger (P286)



DT-171T
Type-K temperature
Datalogger (P285)



DT-173
Sound Level Datalogger (P287)



DT-174B
Humidity/Temperature & Air
Pressure Datalogger (P288)



DT-178A
3-Axis Vibration Datalogger (P289)

DT-194T
Temperature
Datalogger (P284)



CE
EMC
EN: 61326

DT-172
Temperature & Humidity
Datalogger (P286)



DT-193H1
Temperature & Humidity
Datalogger (P283)

DT-175CV1
AC Current & Voltage Datalogger (P220)




DT-100B
Bluetooth Transmitter



DT-1700/1701/1702

Laboratory Temperature & Humidity / Sound Level / CO Datalogger



CE
EMC
EN: 61326

Made for
iPod iPhone iPad

Bluetooth

Features	1700	1701	1702
Humidity & temperature readings, plus Time and Date	*		
Sound Level, humidity & temperature readings, plus Time and Date		*	
Carbon monoxide, humidity & temperature readings, plus Time and Date			*
Measures Humidity & Temperature plus included software calculates and graphs Dew Point, Wet Bulb, and GPP (grains per pound)	*	*	*
Large dual graphical LCD displays with adjustable vertical and horizontal TAC resolution	*	*	*
Internal memory records up to 80 Million data points	*	*	*
7" TFT color LCD indicates percentage of memory remaining	*	*	*
Replaceable probe does not require recalibration	*	*	*
Detachable probe extends up to 1 meter for measurements in closed environments	*	*	*
Audible and visual alarm with Hi/Low setpoints	*	*	*
Output socket used with optional external alarm module	*	*	*
Scroll the cursor to display selected data recorded	*	*	*
Desk or wall mount	*	*	*
Bluetooth interface to smartphone/PC	*	*	*
Smart touchscreen	*	*	*
Sample rate 1 second	*	*	*

Specification	1700	1701	1702
Relative Humidity Range	0 ~ 100.0%	*	*
Temperature Range	-28.0 ~ 60.0°C (-20.0 ~ 140.0°F)	*	*
Accuracy	±3% Relative Humidity; ±1.8°F/±1°C	*	*
Sound level meter		*	*
Sound level Range	Auto: 30dB~130dB (31.5HZ ~ 8kHz)	*	*
Accuracy	±1.4dB (IEC61672 -1 CLASS2)	*	*
Carbon monoxide meter			*
Carbon monoxide Range	0 ~ 1000PPM		*
Accuracy	±5% or ±10 PPM		*

Size(HxWxD): 180mm x 115mm x 18mm Accessories :
Weight: 450g 3.7V Lithium battery, software and clamshell.



Model 1700



CE
EMC
EN: 61326

Model 1701

DT-1703 Desktop Indoor Air Quality CO₂ Monitor

Features

- 7" Color TFT LCD Display
- Checks for Carbon Dioxide (CO₂) concentrations (0 to 9,999ppm) and displays Temperature (14 to 140°F / -10 to 60°C) and Relative Humidity (0.1 to 99.9%) readings
- NDIR (non-dispersive infrared) CO₂ sensor
- Indoor Air Quality displayed in ppm with Good, Normal, Poor indication
- Displays Year, Month, Date, and Time
- Max/Min CO₂ value recall function

CE EMC
EN: 61326

Specifications	Function	Range	Resolution	Accuracy
CO ₂		0-9999ppm	1ppm	±5%±75ppm
Temperature		-10 to 60°C/14 to 140°F	0.1°C/0.1°F	±1°C/1.8°F
Humidity		0.1 to 100.0%RH	0.1%RH	±3%RH(25°C/30 to 99%RH) ±4%RH(25°C/0 to 30%RH)

Size(HxWxD): 205mm x 110mm x 35mm
Weight: 350g
Accessories : NiMH battery, gift box with carrying case.



Model 1703