

TECHNICAL DATA

# Fluke 972B/972ES Temperature Humidity Meter



## Key features

- Standard and optional external probes are available for limited space
- Accuracy of  $\pm 0.5$  °C and  $\pm 3\%$  RH, to meet industrial grade testing requirements
- 99 sets of stored data, easy to review (Fluke 972B only)
- Auto logging mode for up to 8 hours of automatic temperature and humidity monitoring (Fluke 972B only)
- Comfortable grip and ergonomic design
- Reinforced sensor protective cover for worry-free operation

## Product overview: Fluke 972B/972ES Temperature Humidity Meter

Measure-and-view, industrial design, necessity for inspection.

Temperature and humidity are two important items for comfort test of indoor air and environment. The Fluke 972 Series Temperature Humidity Meter can quickly and easily collect accurate humidity and temperature data. It features streamlined industrial design and is comfortable to hold. Simplified buttons require no complicated operations. The selected high-precision sensors ensure that reliable data is collected. The Fluke 972 Series is an indispensable environmental monitoring tool for facility maintenance and engineering technicians, HVAC service contractors, R&D and manufacturing engineers, and professionals involved in indoor air quality (IAQ) assessments.

## Specifications: Fluke 972B/972ES Temperature Humidity Meter

		972B	972ES
<b>Detailed Specifications</b>			
Sensor Type		Internal + External	External
Temperature Measurement Range		Internal sensor: -30.0 °C to 65.0 °C; External sensor: -40.0 °C to 99.9 °C	-40.0 °C to 99.9 °C
Temperature Accuracy		Internal sensor: ±0.5 °C (-30.0 °C to 65.0 °C) External sensor: ±0.5 °C (-30.0 °C to 65.0 °C); ±0.7 °C (others)	±0.5 °C (-30.0 °C to 65.0 °C); ±0.7 °C (others)
Temperature Resolution		0.1 °C	
Dew Point Temperature	Range	-40.0 °C to 99.9 °C	N/A
	Resolution	0.1 °C	N/A
Wet Bulb Temperature	Range	-20.0 °C to 60.0 °C	N/A
	Resolution	0.1 °C	N/A
Humidity	Range	0.0% RH to 99.9% RH	
	Accuracy	±3% RH (≥20.0% RH to ≤80.0% RH @ 25 ℹ) ±5% RH (≥1% RH to <20% RH, >80% RH to ≤95% RH @ 25ℹ) Unspecified for others	
	Resolution	0.1% RH	
Data Storage		Yes. Up to 99 sets	N/A
Display		2-line LCD display, with backlight	No
Auto-off		Power off after 20 min without any operation	N/A
Max/Min/Avg		Yes	N/A
Auto Logging Mode		Yes	N/A
<b>General Specifications</b>			
Temperature	Operating	-30 °C to 70 °C	-40 °C to 70 °C
	Storage	-30 °C to 70 °C, <80% RH (without battery)	-40 °C to 70 °C, <80% RH
Altitude	Operating	2000 m	
	Storage	12 000 m	
Relative Humidity	Operating	0% RH to 99% RH	
	Storage	ℹ80% RH	
Power Supply	Battery Type	2 x AAA Batteries	—
	Battery Life	1000 hrs for continuous operating, backlight off	—
Safety		IEC61010-1, Pollution Degree 2	
Dimensions (L x W x H)		211 × 58 × 40 mm	264 × 33 × 28 mm
Weight		172 g (body)	127 g

Electromagnetic Environment (EMC)	<p>IEC 61326-1: Portable, Electromagnetic Environment; IEC 61326-2-2; CISPR 11: Group 1; Class A</p> <p>Group 1: Equipment intentionally generates and/or uses conductive-coupled RF energy, which is necessary for its internal operation.            Class A: Equipment is suitable for use in all establishments other than domestic and those directly connected to a low-voltage power supply network that supplies buildings used for domestic purposes. There may be potential difficulties in ensuring electromagnetic compatibility in other environments due to conducted and radiated disturbances.            Caution: This equipment is not intended for use in residential environments and may not provide adequate protection to radio reception in such environments.</p>
IP Rating	IEC 60529: IP30, non-operating

## Ordering information



### **Fluke 972B/972ES**

Fluke 972B/972ES Temperature Humidity Meter

---

Fluke 972B Temperature Humidity Meter

Includes

- The Fluke 972B Temperature Humidity Meter
- Fluke 972ES external sensor

Fluke 972ES External temperature/humidity sensor

Includes

- Fluke 972ES external sensor
-

Fluke. *Keeping your world up and running.*®

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Europe/M-East/Africa  
+31 (0)40 267 5100  
In Canada (800)-36-FLUKE  
From other countries +1 (425) 446-5500

**BUT. FLUKE SOUTH EAST ASIA PTE LTD**  
Menera Satu Sentra Kelapa Gading #06-05  
JI. Bulevar Kelapa Gading Kav. LA# No. 1  
Summarecon Kelapa Gading  
Jakarta Utara 14240  
Indonesia  
Tel: +62 21 2938 5922  
Email: info.asean@fluke.com  
www.fluke.com/id-en  
©2024 Fluke Corporation. Specifications subject to  
change without notice.  
04/2024

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**