

TECHNICAL DATA

Fluke AC280 SureGrip™ Hook Clips



Key features

- One pair of nickel-plated clips (red, black) with a profile narrowing to 5.6 mm at the tip and a hook opening of 6.4 mm at the front, reducing to 2 mm at the base
- Provides reliable and secure connections for precise electrical measurements
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 3 A
- Recommended for use with TL222 and TL224 test leads

Product overview: Fluke AC280 SureGrip™ Hook Clips

SureGrip™ accessories are designed to improve steadiness in slippery hands. Rubber overmolded surfaces and finger-hugging curves give the user a comfortable, reliable grip on the accessory so they can focus on making an accurate measurement.

Ordering information



Fluke AC280

Fluke AC280 SureGrip™ Hook Clips

Fluke. *Keeping your world up and running.*®

Fluke Europe B.V.

P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com/en

©2024 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
04/2024

For more information call:

In Middle East/Africa
+31 (0)40 267 5100

**Modification of this document is not permitted
without written permission from Fluke Corporation.**