

8093 HUMIDITY-TEMPERATURE SENSOR



Low power consumption

Aloft or at the roadside, is where this humidity-temperature sensor (8093.1) is most commonly used. The instrument is characterised by the high-quality measuring elements, robust housing, reliable membrane filter and low-current electronics. Thus the sensor (8093.1) is especially suitable for meteorological outdoor measurements in very diverse application fields.

- Small, light, compact
- Easy installation, robust, nearly maintenance free
- Low power consumption
- Good dynamical behaviour
- Reliable membrane filter as protection against pollutants
- High long-term stability and nearly linear characteristic line

APPLICATIONS

- Building technology
- Traffic systems
- Automatic weather stations
- Buoys
- Agricultural weather stations
- Energy supply and disposal systems
- Environmental measurement technology

Professional Line	8093
Id-No.	00.08093.100000
Meas. range air temperature	-30...+70 °C
Meas. range rel. humidity	0...100 % r. F.
Accuracy air temperature	± 0.2 °C at -27...+70 °C; Plus: ± 0.007 °C at +10 °C and > +40 °C
Accuracy rel. humidity	± 2 % r. h. at 5...95 % r. h. • +10...+40°C; Plus: 0.1 % r. h./ °C at +10°C and > +40°C
Response time	Humidity: 20 s (without wind and without filter, otherwise at 1.5 m/s: 1.5 min)
Long-term stability	typical under normal conditions 1% r. h./ year
Output	0...1 VDC = 0...100% r. h. • min. load resistance ≥ 2.5 kΩ • Pt100 (4-wire circuit)
Supply voltage	10...30 VDC
Power consumption	1 mA
Measuring elements	capacitive • Pt100 1/3 DIN • IEC 751 class B
Dimensions	H 122 mm • Ø 20 mm
Housing	aluminium • lacquered • grey-white
Protection class	IP 65 • membrane filter as sensor protection IP 30
Weight	approx. 0.3 kg

0082-2 • EN 55011 Cl. B

PRODUCT-VIEW

Accessories (order separately)

5 m cable

00.08141.600000 Sensor shelter with natural ventilation

00.08141.600004 Sensor shelter with artificial ventilation



AN **aem** BRAND

As of: 13.07.2023