



LDM-300/350/380

Mini Laser Distance Meter:

- Area, Volume Calculations
- Indirect Measurement Using Pythagoras
- Addition/Subtraction
- Continuous Measurement
- Min/Max Distance Tracking
- Timer (self-triggering)
- Laser Continuous
- Stake-out Function
- Display Illumination and Multi-line Display
- Buzzer Indication
- Multifunctional Endpiece
- Bluetooth Interface
- Meterbox iLDM & Cloud Service



Features	LDM-300	LDM-350	LDM-380
3.5" TFT Color LCD Display		*	*
Built-in Camera			*
Images (JPEG) & Video (3GP)			*
Micro SD Memory Card & Datalogger Function			*
Electrical Compass		*	*
Angle Measurement Using Tilt Sensor ($\pm 90^\circ$)		*	*
Area, Volume Calculations	*	*	*
Indirect Measurement Using Pythagoras	*	*	*
Addition/Subtraction	*	*	*
Continuous Measurement	*	*	*
Min/Max Distance Tracking	*	*	*
Timer (self-triggering)	*	*	*
Laser Continuous	*	*	*
Stake-out Function	*	*	*
Display Illumination and Multi-line Display	*	*	*
Buzzer Indication	*	*	*
Multifunctional Endpiece	*	*	*
Bluetooth Interface	*	*	*
Meterbox iLDM & Cloud Service	*	*	*

Size(HxWxD): 138mm x 55mm x 35mm

Weight: 165g

Specifications	LDM-300	LDM-350	LDM-380
Measuring Range	0.05 to 100m (0.15ft to 328.0ft)	0.05 to 150m (0.15ft to 492.0ft)	0.05 to 200m (0.15ft to 656.0ft)
Measuring Accuracy	Typically $\pm 1.5\text{mm}$ ($\pm 0.06\text{in}$)	Typically $\pm 1.5\text{mm}$ ($\pm 0.06\text{in}$)	Typically $\pm 1.5\text{mm}$ ($\pm 0.06\text{in}$)
Smallest Unit Displayed	1mm	1mm	1mm
Measuring Units	m, in, ft	m, in, ft	m, in, ft
Laser Class	Class II 635nm, <1mW	Class II 635nm, <1mW	Class II 635nm, <1mW
Range of Bluetooth	10m	10m	10m
Camera Pixels			5Mega
Compass Measuring Range		0-360°	0-360°

Compass Measuring Accuracy		$\pm 2^\circ$	$\pm 2^\circ$
Tilt Sensor Measuring Range	$\pm 90^\circ$	$\pm 90^\circ$	$\pm 90^\circ$
Tilt Sensor Measuring Accuracy		$\pm 0.5^\circ$	$\pm 0.5^\circ$
Dust Protect/Splash Proof	IP54	IP54	IP54
History Measurement Records	99	99	99
Keyboard Type	Super Soft-touch (Long Life)	Super Soft-touch (Long Life)	Super Soft-touch (Long Life)
Operating Temperature	-10°C to 50°C (14°F to 122°F)	-10°C to 50°C (14°F to 122°F)	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 70°C (4°F to 158°F)	-20°C to 70°C (4°F to 158°F)	-20°C to 70°C (4°F to 158°F)
Battery Life	Up to 8,000 Measurements	Up to 5,000 Measurements	Up to 5,000 Measurements
Auto Laser Switch-off	After 0.5min	After 0.5min	After 0.5min
Auto Instrument Switch-off	After 3min	After 3min	After 3min

Accessories:

2 x 1.5V "AAA" batteries and gift box with carrying case.